



FT 380 Former

Description

Ceramic former used for the production of dipped latex, nitrile and other synthetic gloves.

Process Flow

1. Testing Materials
2. Grinding & compounding
3. Casting
4. Surface treating
5. Making texture
6. Kilning
7. Inspection
8. Packing & Storage
9. Shipping

Technical Specification

Dimension Tolerance (mm)	Height	+/- 3
	Finger Length	+/- 2
	Finger Circumference	+/- 2
Wall Thickness (mm)	Standard	2.5~4.0
	Tolerance	+/- 0.5
Properties	Water Absorption	≈ 0.12%
	Alkali Resistance	≥ 99.7%
	Heat Resistance	>180°C
	Porosity	≈ 0.34%
	Bulk Density	≈ 2.57g/cm ³
	Moh's Hardness	≈ 8

Packaging

24pcs per carton.

Revision : 1.0 Issue Date : 5 Mac 2020

Page 1- FT 380 Former

LEXIS SPECIALTIES SDN. BHD. (REG. NO.:1282200-P)

NO. 8, LORONG SUNGAI PULOH 7/KU6, KAWASAN PERINDUSTRIAN SUNGAI PULOH, 42100 KLANG,
SELANGOR DARUL EHSAN, MALAYSIA.

TEL: +603-3292 8779 / 3292 9778