

Technical Data Sheet

Product : TecXa MP(PK)

Revision : 1.2

TecXa MP(PK)

Product Introduction:

TecXa MP(PK) is binder free aqueous

Pigment	Red, Aluminium Metallic Pigment
Carrier	Water and Glycol
Pigment Contain	30-35%
Glycol Contain	15-20%
Heavy Metal Contain	Nil

Physical Properties:

Appearance	Metallic Pink viscous liquid
Light fastness (Deep Shade)	8 (1:poor ; 8:excellent)
Acid Resistance	5 (1:poor ; 5:excellent)
Alkaline Resistance	5 (1:poor ; 5:excellent)
Viscosity	< 1500 mPas
Color Strength (weight)	95 - 105
Delta E	< 1

Handling Precautions:

Care should be taken to ensure that workers use safety face mask or other eye protection in the course of handling as any contact with the human skin, eyes, etc. could results in severe irritation, burns and injury.

In case of eye contact, flush with plenty of water and seek prompt medical attention.

Transportation Handling:

TecXa MP(PK) should be stored in a cool well-ventilated area away from sunlight and heat.

Storage and Packing:

TecXa MP(PK) must be stored in closed storage area, protected from direct sunlight and best at temperature below 35°C. It is in 20kg/pail, 100kg/drum and 200kg/drum packing.

Please contact the representative of **Lexis Specialties Sdn Bhd** for more information.